

EVENSON, McKEOWN, EDWARDS & LENAHAAN, P.L.L.C.  
1200 G Street, N.W., Suite 700  
Washington, D.C. 20005  
(202) 628-8800

September 11, 2000

JCS20 U.S. PTO  
09/659066  
09/11/00

Box PATENT APPLICATION

Commissioner for Patents  
Washington, D.C. 20231

Re: New U.S. Patent Appln.  
Our Ref: 1420/49237

Sir:

Transmitted herewith for filing is the patent application of:

Yoshikazu HIRAYAMA and Yoshiyuki KOBAYASHI

entitled: VOICE REFERENCE APPARATUS, RECORDING MEDIUM RECORDING  
VOICE REFERENCE CONTROL PROGRAM AND VOICE RECOGNITION  
NAVIGATION APPARATUS


Enclosed are:

1. Specification, including 11 claims (43 pages).
2. 12 Sheets of formal drawings showing Figs. 1, 2a-2c, 3, 4a-4b, 5-7, 8a-8c, 9-10, 11a-11d.
3. X Declaration and Power of Attorney (**executed**).
4. Assignment of the invention to Xanavi Informatics Corporation.
5. Certified copy of Priority Document 11-255981 filed in Japan on September 9, 1999, the priority of which is being claimed under 35 U.S.C. §119 and 37 C.F.R. §1.55.
6. X Information Disclosure Statement w/1 reference.
7. The filing fee has been calculated as shown below:

Basic Fee				\$345/690 =	\$690.00
Total Claims	<u>11</u>	- 20 =	<u>0</u>	x \$ 9/18 =	\$
Independent Claims	<u>4</u>	- 3 =	<u>1</u>	x \$39/78 =	\$ 78.00
Multiple Dependent Claim Presented				\$130/260 =	\$
Total Filing Fee					<u>\$768.00</u>

Two checks in the amount of \$768.00 for the filing fee and \$40.00 for the assignment recording fee are enclosed. The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment, to Deposit Account No. 05-1323 (Docket #1420/49237). A duplicate copy of this sheet is enclosed.

Respectfully submitted,

  
Jeffrey D. Sanok  
Reg. No. 32,169

VOICE REFERENCE APPARATUS,  
RECORDING MEDIUM RECORDING VOICE REFERENCE CONTROL PROGRAM  
AND VOICE RECOGNITION NAVIGATION APPARATUS

5 INCORPORATION BY REFERENCE

The disclosure of the following priority application  
is herein incorporated by reference:

Japanese Patent Application No. 11-255981 filed  
September 9, 1999

10

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a voice reference  
system and a voice recognition navigation apparatus using  
15 the voice reference system.

2. Description of the Related Art

There are car navigation apparatuses (hereafter  
referred to as navigation apparatuses) that display the  
current position of the vehicle, display a map over a wide  
20 area or in detail and provide guidance to the driver along  
the traveling direction over the remaining distance to the  
destination in the prior art. There are also voice  
recognition navigation apparatuses in the prior art having  
a function of enabling the driver engaged in driving to  
25 issue operating instructions by voice to improve driver

safety (see Japanese Laid-Open Patent Publication No. 09-292255, for instance).

FIGS. 11A ~ 11D illustrate the concept of voice recognition dictionaries (hereafter simply referred to as  
5 dictionaries) used in a navigation apparatus in the prior art to display a desired ski resort in a map through voice instructions.

When the power to the navigation apparatus is turned on, the basic dictionary shown in FIG. 11A is opened in the  
10 memory. In the basic dictionary, instruction phrases such as "bird's eye view display," "enlarge," "reduce" and "ski resorts" are stored as recognition words. If the user says (vocalizes) "ski resorts" to specify a facility category, voice recognition processing is performed on all  
15 the recognition words in the basic dictionary. When "ski resorts" is recognized as the result of the voice recognition processing, a ski resort prefecture name dictionary, which contains prefecture names where ski resorts are present as recognition words is opened in  
20 memory, as shown in FIG. 11B.

Then, if the user says "ABCD Prefecture," for instance, to specify the prefecture where the desired ski resort is present, voice recognition processing is performed on all the recognition words in the prefecture  
25 name dictionary. If "ABCD Prefecture" is recognized as

the result of the voice recognition processing, an ABCD Prefecture ski resort name dictionary containing the names of ski resorts present in ABCD Prefecture as recognition words is opened in memory as shown in FIG. 11C. Next, the user says "B Ski Resort" to specify a ski resort, and in response, voice recognition processing is performed on all the recognition words in the ABCD Prefecture ski resort name dictionary. After "B Ski Resort" is recognized through the voice recognition processing, a map containing B Ski Resort is displayed on the screen of the navigation apparatus as shown in FIG. 11D.

In addition to ski resorts, there are various facility categories that need to be recognized by the voice recognition software program, such as theme parks and airports. Many of such facilities are located near prefectural borders. For instance, there is a ski resort located near the prefectural border of Gunma Prefecture and Niigata Prefecture, a theme park located near the prefectural border of Tokyo Prefecture and Chiba Prefecture and an airport located near the prefectural border of Osaka Prefecture and Hyogo Prefecture. In addition, in the case of a vast facility such as a golf course or a ski resort, the user may not be certain which prefecture the facility belongs to.

If the user inputs the wrong prefecture when

specifying the prefecture where the facility is located in  
such a situation, the facility name dictionary in the wrong  
prefecture where the facility is not located is opened in  
memory and accessed. Thus, a problem occurs in that a  
5 successful recognition is not achieved no matter how many  
times the user subsequently says the accurate facility name.

#### SUMMARY OF THE INVENTION

An object of the present invention is to provide a  
10 voice reference apparatus capable of performing a search  
for a reference target through voice recognition quickly,  
efficiently and accurately with a high degree of  
reliability and a recording medium that records a control  
program used in the process. More specifically, the  
15 object of the present invention is to provide a voice  
recognition navigation apparatus capable of achieving  
accurate voice recognition of the names of facilities  
located near the borders of public administrative zones  
(districts).

20 In order to attain the above object, a voice reference  
apparatus according to the present invention that  
classifies a plurality of search targets into a plurality  
of division blocks, searches for a search target by first  
specifying a division block and then specifying the search  
25 target and enables specification of, at least, the search

target to be made by voice, comprises: a first storage device in which recognition data related to search targets corresponding to individual division blocks are stored; a second storage device in which division block-related information indicating one or more other division blocks related to a given division block through a specific relationship is stored; a recognition data selection device that selects recognition data corresponding to only a certain division block and one or more other division blocks related to the certain division block specified by the division block-related information from the first storage device, when the certain division block has been specified; and a voice recognition processing device that performs voice recognition based upon voice recognition data generated by using the recognition data selected by the recognition data selection device and audio data corresponding to the search target specified by voice.

In this voice reference apparatus, it is preferred that: the plurality of division blocks are public administrative zones; the search target is located in one of the public administrative zones; and the division block-related information indicates one or more other public administrative zones related to a specified public administrative zone through a specific relationship. In this case, it is preferred that: the public administrative

zones are each constituted of a prefecture, a state or a country. Also, it is preferred that the division block-related information indicates one or more other public administrative zones adjacent to a specified public administrative zone. In this case, it is preferred that the recognition data related to the search target includes information related to a public administrative zone in which the search target is located. Furthermore, it is preferred that a display control device that implements control to display details related to results of a search of the search target on a display device is further provided, and when implementing control to display the details related to the results of the search of the search target, the display control device also displays on the display device information related to the public administrative zone in which the search target is located.

A voice recognition navigation apparatus according to the present invention, comprises: a voice reference apparatus; a map information storage device that stores map information; and a control device that implements control for providing route guidance based upon, at least, results of a search performed by the voice reference apparatus and the map information. And the voice reference apparatus, which classifies a plurality of search targets into a plurality of division blocks, searches for a search target

by first specifying a division block and then specifying the search target and enables specification of, at least, the search target to be made by voice, comprises: a first storage device in which recognition data related to search  
5 targets corresponding to individual division blocks are stored; a second storage device in which division block-related information indicating one or more other division blocks related to a given division block through a specific relationship is stored; a recognition data selection device  
10 that selects recognition data corresponding to only a certain division block and one or more other division blocks related to the certain division block specified by the division block-related information from the first storage device, when the certain division block has been  
15 specified; and a voice recognition processing device that performs voice recognition based upon voice recognition data generated by using the recognition data selected by the recognition data selection device and audio data corresponding to the search target specified by voice.

20 A recording medium according to the present invention that records a voice reference control program for searching for a search target specified by voice, by first specifying a division block and then specifying the search target. The control program comprises: an instruction for  
25 reading recognition data related to search targets, a



plurality of the search targets being classified into a plurality of division blocks; an instruction for reading data related to division block-related information indicating one or more other division blocks related to a given block through a specific relationship; an instruction for selecting recognition data corresponding to only a certain division block and one or more other division blocks related to the certain division block specified by the division block-related information when the certain division block has been specified; and an instruction for implementing a voice recognition based upon voice recognition data generated by using the recognition data that have been selected and audio data corresponding to the search target specified by voice.

15 A data signal according to the present invention is transmitted in a communication line and comprises a voice reference control program for searching for a search target specified by voice, by first specifying a division block and then specifying the search target. And the control  
20 program comprises: an instruction for reading recognition data related to search targets, a plurality of the search targets being classified into a plurality of division blocks; an instruction for reading data related to division block-related information indicating one or more other  
25 division blocks related to a given block through a specific

relationship; an instruction for selecting recognition data  
corresponding to only a certain division block and one or  
more other division blocks related to the certain division  
block specified by the division block-related information  
5 when the certain division block has been specified; and an  
instruction for implementing a voice recognition based upon  
voice recognition data generated by using the recognition  
data that have been selected and audio data corresponding  
to the search target specified by voice.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates the structure assumed by the car  
navigation system according to the present invention in a  
first embodiment;

15 FIGS. 2A ~ 2C show recognition dictionaries related to  
the ski resort category among recognition dictionaries used  
in the first embodiment;

FIG. 3 shows a neighboring prefecture table;

20 FIGS. 4A and 4B present an example of how neighboring  
prefectures may be assigned for each prefecture;

FIG. 5 is a flowchart of the control implemented to  
reference the name of a facility in a given prefecture;

FIG. 6 is a flowchart continuing from the flowchart in  
FIG. 5;

25 FIG. 7 is a flowchart continuing from the flowchart in

FIG. 6;

FIGS. 8A ~ 8C show recognition dictionaries related to the ski resort category among recognition dictionaries used in a second embodiment, presenting an example in which an area is divided in units of individual states;

FIG. 9 presents a neighboring state table;

FIG. 10 illustrates how the program may be provided via a transmission medium; and

FIGS. 11A ~ 11D illustrate the concept of the voice recognition dictionaries used in a navigation apparatus in the prior art to display a map containing a desired ski resort through voice instruction.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

##### - First Embodiment -

FIG. 1 shows the structure adopted by the car navigation system in the first embodiment of the present invention. The car navigation system comprises a navigation apparatus 100 and a voice unit 200.

The navigation apparatus 100 comprises a GPS receiver 101, a gyro sensor 102, a vehicle speed sensor 103, a driver 104, a CPU 105, a RAM 106, a ROM 107, a CD-ROM drive 108, a display device 109, a bus line 110 and the like.

The voice unit 200 comprises a microphone 201, an A/D conversion unit 202, a D/A conversion unit 203, an

amplifier 204, a speaker 205, a TALK switch 206, a driver 207, a CPU 208, a RAM 209, a ROM 210, a bus line 212 and the like. The navigation apparatus 100 and the voice unit 200 are connected with each other via a communication line 211.

The GPS receiver 101 receives a signal from a GPS (Global Positioning System) satellite and detects the absolute position and the absolute bearing of the vehicle. The gyro sensor 102, which may be constituted of, for instance, a vibrating gyro, detects the yaw angle speed of the vehicle. The vehicle speed sensor 103 detects the distance traveled by the vehicle based upon the number of pulses output each time the vehicle has traveled over a specific distance. The two dimensional movement of the vehicle is detected by the gyro sensor 102 and the vehicle speed sensor 103. The driver 104 is provided to connect signals from the GPS receiver 101, the gyro sensor 102 and the vehicle speed sensor 103 with the bus line 110. In other words, the outputs from the individual sensors are converted to data that can be read by the CPU 105.

The CPU 105 controls the entire navigation apparatus 100 by executing a program stored in the ROM 107. In the RAM 106, which is constituted of volatile memory, a work data area is secured. In the ROM 107 constituted of non volatile memory, the control program mentioned above and

the like are stored. The CD-ROM drive 108 uses a CD-ROM 111 as a recording medium to store road map information such as vector road data and the like. The CD-ROM drive may be alternatively constituted of another recording  
5 device such as a DVD drive which uses a DVD as a recording medium. The display device 109 displays a road map that contains the current position and the surrounding area of the vehicle, route information indicating the route to the destination, the intersection information indicating the  
10 next intersection to which the vehicle is to be guided and the like. It may be constituted of, for instance, a liquid crystal display device or a CRT. The bus line 110 is provided to connect the components of the navigation apparatus 100 such as the CPU 105 via a bus.

15 The voice unit 200 performs voice-related processing such as voice recognition and voice synthesis. The TALK switch 206 is pressed by the user to give an instruction for a start of voice recognition. Audio data are input via the microphone 201 over a specific period of time after  
20 the TALK switch 206 is pressed. The sound thus input is converted to digital audio data by the A/D conversion unit 202 and the driver 207.

In the ROM 210 of the voice unit 200, a voice  
recognition software program, a voice synthesis software  
25 program, voice recognition dictionaries (hereafter simply

referred to as recognition dictionaries), a voice synthesis dictionary (hereafter simply referred to as a synthesis dictionary) and the like are stored. In the voice recognition software program, correlation values between the digital audio data and all the recognition words in a recognition dictionary are calculated and the recognition word achieving a largest correlation value is determined to be the recognition results. In the voice synthesis program, data needed to output a specified phrase through the speaker are calculated. Since both software programs are of the known art, their detailed explanation is omitted.

A recognition dictionary is constituted of a set of data compiled with a plurality of words and phrases to be used in voice recognition. More specifically,

pronunciation data corresponding to individual words specified with Hiragana , Katakana, Roman characters or phonetic symbols (the corresponding character codes, in reality) are stored in the recognition dictionary. The words and phrases stored in the recognition dictionary are referred to as recognition words. The character data corresponding to the recognition word and information such as the corresponding coordinate information if the recognition word represents a facility name as well as the pronunciation data are attached to each recognition word.

Details of the recognition dictionaries are to be given

later. In the synthesis dictionary, sound source data and the like necessary for voice synthesis are stored.

When a speech is completed, the CPU 208 executes the voice recognition software program by using the RAM 209, the ROM 210 and the like to perform a voice recognition of the digital audio data. The voice recognition software program references the pronunciation data (data specified in Hiragana, Katakana or Roman characters) of the recognition words in the recognition dictionary to generate the voice recognition data corresponding to the recognition words and calculates the correlation values between the voice recognition data and the digital audio data. It calculates the correlation values between all the recognition words and the digital audio data and determines the recognition word achieving the highest correlation value which is also equal to or larger than a specific value before ending the voice recognition. The echo-back word linked to the recognition word is then converted to special speech data by using the voice synthesis software program. Then, the CPU 208 engages the D/A conversion unit 203, the amplifier 204 and the speaker 205 to output the recognition results through echo-back.

If all the correlation values thus calculated are equal to or smaller than the specific value, the CPU 208 decides that voice recognition has failed and thus no

navigation operation is executed. More specifically, it may sound a beep indicating that a voice recognition attempt has failed or it may sound a response echo-back such as "recognition failed." The bus line 212 is  
5 provided for the voice unit 200.

Next, a detailed explanation is given on the recognition dictionaries. The recognition dictionaries include a basic dictionary containing recognition words related to instructions, prefecture name dictionaries  
10 containing recognition words related to prefecture names corresponding to various categories and prefecture facility name dictionaries each containing recognition words related to the names of facilities in a given prefecture in a given category. The prefecture names used to specify  
15 prefectures, too, should be regarded as a type of instruction phrase.

FIGS. 2A ~ 2C show recognition dictionaries related to the ski resort category among the recognition dictionaries. The basic dictionary shown in FIG. 2A is a dictionary  
20 commonly used among various categories, and contains recognition words related to instructions such as "bird's eye view display," "enlarge ," "reduce" and "ski resorts." In the ski resort prefecture name dictionary shown in FIG. 2B, recognition words related to the names of prefectures  
25 where ski resorts are present are stored. In the ABCD



Prefecture ski resort name dictionary shown in FIG. 2C, recognition words related to the names of ski resorts located in ABCD Prefecture are stored, whereas in the EFGH Prefecture ski resort name dictionary in FIG. 2C, 5 recognition words related to the names of ski resorts present in EFGH Prefecture are stored. In addition to the ABCD Prefecture ski resort name dictionary and the EFGH Prefecture ski resort name dictionary in FIG. 2C, ski resort dictionaries corresponding to the individual 10 prefectures listed in the ski resort prefecture name dictionary in FIG. 2B are provided.

A recognition word is constituted of pronunciation data for a given phrase, it is specified by hiragana, katakana, Roman character, pronunciation symbol or the like 15 and the corresponding character code or the like is stored as the recognition word, the items in FIGS. 2A ~ 2C are expressed using Kanji and the like to facilitate the explanation.

It is to be noted that the names of ski resorts in the 20 entire country are stored in a hierarchical structure in units of individual prefectures for the following reason. Let us assume that a single ski resort name dictionary, in which the names of all the ski resorts in the country are stored, is provided without the ski resort prefecture name 25 dictionary in FIG. 2B. In this case, for each ski resort

name to be recognized through voice recognition, all the ski resort names in the recognition dictionary must undergo the voice recognition processing and a great deal of time will be required for the processing. In addition, since  
5 the number of items to undergo recognition processing is large, the chance of erroneous recognition rises. Furthermore, the entire recognition dictionary may not be opened in the memory at once due to limits imposed on the work memory capacity. Thus, the names of ski resorts in  
10 the country are stored in the hierarchical structure in units of individual prefectures and are processed as described above.

If the golf course category is specified, a golf course prefecture name dictionary and golf course name  
15 dictionaries corresponding to the individual prefectures are prepared (not shown). The dictionaries related to other categories such as theme parks are prepared in a similar manner. In other words, as recognition  
20 dictionaries, the basic dictionary, prefecture dictionaries in various categories and facility name dictionaries corresponding to the individual prefectures in each category are prepared.

In this embodiment, a neighboring prefecture table is stored in the ROM 210 in addition to the recognition  
25 dictionaries. FIG. 3 presents the neighboring prefecture

table. a neighboring prefecture table 301 contains neighboring prefecture information for each of the 47 prefectures in the country (in case of Japan).

Neighboring prefecture information 302 for each prefecture  
5 includes data indicating a prefecture code 303 which represents the target prefecture itself, the number of neighboring prefectures 304 and neighboring prefecture codes 305.

Any of various methods may be adopted to assign  
10 neighboring prefectures. For instance, all the prefectures geographically adjacent to a given prefecture at its prefectural border may be assigned, prefectures that are considered to be nearby may be assigned, prefectures which should be regarded as neighboring prefectures as  
15 dictated by experience may be assigned or prefectures located along an expressway passing through the prefecture may be assigned as neighboring prefectures. FIGS. 4A and 4B present an example of neighboring prefectures assigned for the individual prefectures in Japan.

20 In the embodiment, if a given prefecture name is specified by voice when searching for a facility in a given category, the neighboring prefecture table described above is employed and the facility name dictionary corresponding to a neighboring prefecture of the specified prefecture,  
25 too, is opened in memory. As a result, when searching

for a facility located near the prefectural border, it can be found with ease even if a neighboring prefecture is specified by mistake.

FIGS. 5 ~ 7 present a flowchart of the control implemented to search for the name of a facility located in a given prefecture on the voice unit 200. Now, an explanation is given on a specific example in which ABCD Prefecture is erroneously specified when searching for F Ski Resort located in EFGH Prefecture adjacent to ABCD Prefecture. The control program, which is stored in the ROM 210, is executed by the CPU 208. The routine is started up by turning on the power to the navigation apparatus 100 and the voice unit 200.

In step S1, the basic dictionary shown in FIG. 2A stored in the ROM 210 is read out and opened in the RAM 209. The basic dictionary in the ROM 210 is opened in the RAM 209 to increase the processing speed. If the processing speed is not a crucial issue, the dictionary in the ROM 210 may be accessed directly. In step S2, a decision is made as to whether or not the TALK switch 206 has been pressed, and if it is decided that the TALK switch 206 has been pressed, the operation proceeds to step S3. If, on the other hand, it is decided that the TALK switch 206 has not been pressed, the routine ends. After pressing the TALK switch 206, the user says (vocalizes), for instance, "ski

resorts" within a specific period of time. In step S3, the audio signal obtained through the microphone 201 is converted to digital audio data. In step S4, a decision is made as to whether or not the speech has ended. A  
5 speech is judged to have ended when the audio signal lapses over a specific length of time. If it is decided that the speech has ended, the operation proceeds to step S5, whereas if it is decided that the speech has not ended, the operation returns to step S3. In this example, digital  
10 audio data corresponding to "ski resorts" are obtained in step S3.

In step S5, the correlation values between the digital audio data that have been obtained and all the recognition words in the basic dictionary are calculated before the  
15 operation proceeds to step S6. Namely, the correlation values between the digital audio data corresponding to "ski resorts" obtained in step S3 and the recognition words such as "bird's eye view display," "enlarge," "reduce," "ski resorts" and "golf courses" are calculated. In step S6, a  
20 decision is made as to whether or not the largest correlation value among the calculated correlation values is equal to or larger than a specific value. If it is determined to be equal to or larger than the specific value, it is assumed that the word or phrase has been recognized  
25 and the operation proceeds to step S7. In this example,

the correlation value relative to the recognition word "ski resorts" is the largest. If the correlation value is equal to or larger than the specific value, it is decided that the phrase "ski resorts" has been recognized and a successful search of the category name has been achieved.

In step S7, a voice message constituted of the recognition word that has achieved the largest correlation value and "say the prefecture name" is output. In the example, a message "ski resorts," "say the prefecture name" is echoed back by voice. In addition, the prefecture name dictionary in the relevant category is prepared in the RAM 209 in step S7. In the example, the "ski resort prefecture name dictionary" (see FIG. 2B) is opened in the RAM 209.

If, on the other hand, the largest correlation value is determined to be smaller than the specific value in step S6, it is assumed that the spoken word or phrase has not been recognized and the operation proceeds to step S8. In step S8, a voice message "recognition failed" is echoed back before the processing ends. The navigation apparatus 100 does not engage in any processing.

When the processing in step S7 is completed, the operation proceeds to step S9. In step S9, the audio signal obtained through the microphone 201 is converted to digital audio data as in step S3. In step S10, a decision

is made as to whether not the speech has ended as in step  
S4. During this interval, the user says "ABCD  
Prefecture." By repeating steps S9 and S10, the digital  
audio data corresponding to "ABCD Prefecture" are obtained  
5 in the example.

In step S11, the correlation values between the  
digital audio data thus obtained and all the recognition  
words in the ski resort prefecture name dictionary are  
calculated before the operation proceeds to step S12.  
10 Namely, the correlation values between the digital audio  
data corresponding to "ABCD Prefecture" obtained in step S9  
and the recognition words such as "Hokkaido," "Aomori  
Prefecture," "ABCD Prefecture," "EFGH Prefecture" and  
"Okinawa Prefecture" are calculated. In step S12, a  
15 decision is made as to whether or not the largest  
correlation value among the calculated correlation values  
is equal to or larger than a specific value. If, it is  
decided to be equal to or larger than the specific value,  
it is concluded that the word has been recognized and the  
20 operation proceeds to step S13. In the example, the  
correlation value relative to the recognition word "ABCD  
Prefecture" is the largest. If this correlation value is  
equal to or larger than the specific value, the phrase  
"ABCD Prefecture" has been recognized and the ski resort  
25 prefecture name has been successfully referenced. In step

S13, a voice message constituted of the recognition word that has achieved the largest correlation value and "say the facility name" is output. In the example, "ABCD Prefecture. Say the facility name" is echoed back.

5 In addition, the facility name dictionary for the target prefecture and the facility name dictionary for a neighboring prefecture are opened in the RAM 209 in step S13. Since the name of the target prefecture has been obtained in step S12, the neighboring prefecture table (see  
10 FIG. 3) stored in the ROM 210 is accessed to obtain the neighboring prefecture information for the target prefecture. Based upon the neighboring prefecture information, the facility name dictionary corresponding to a neighboring prefecture is opened in the RAM 209. As a  
15 result, the target prefecture facility name dictionary and a neighboring prefecture facility name dictionary are incorporated and are prepared in the RAM 209 as if they constitute a single target prefecture facility name dictionary. In the example, in which EFGH Prefecture is a  
20 neighboring prefecture of ABCD Prefecture, "ABCD Prefecture ski resort name dictionary" and "EFGH ski resort name dictionary" are incorporated and prepared in the RAM 209.

It is to be noted that if the ROM 210 is accessed directly instead of opening the prefecture facility name  
25 dictionaries in the ROM 210 in the RAM 209, the target



prefecture facility name dictionary and the neighboring  
prefecture facility name dictionary alone may be accessed  
sequentially.

If, on the other hand, it is decided in step S12 that  
5 the largest correlation value is smaller than the specific  
value, it is decided that the spoken word or phrase has not  
been recognized and the operation proceeds to step S14.

In step S14, a voice message "recognition failed" is echoed  
back and the processing ends. The navigation apparatus

10 100 does not engage in any processing.

After the processing in step S13 is completed, the  
operation proceeds to step S15. In step S15, the audio  
signal obtained through the microphone 201 is converted to  
digital audio data as in step S3. In step S16, a decision

15 is made as to whether not the speech has ended as in step  
S4. The user says, for instance, "F Ski Resort" during  
this interval. While the F Ski Resort is actually located  
in EFGH Prefecture, the user erroneously believes that the  
F Ski Resort is in ABCD Prefecture, since it is located  
20 near the prefectural border of ABCD Prefecture and EFGH  
Prefecture. By repeating step S15 and step S16, the  
digital audio data corresponding to "F Ski Resort" are  
obtained.

In step S17, the correlation values between the  
25 digital audio data that have been obtained and all the

recognition words in the facility name dictionaries prepared in the RAM 209 are calculated, and the operation proceeds to step S18. As explained earlier, the facility name dictionary corresponding to the target prefecture and the facility name dictionary corresponding to the neighboring prefecture are prepared in the RAM 209, and the correlation values relative to all the recognition words in these dictionaries are calculated. In the example, correlation values between the digital audio data corresponding to "F Ski Resort" obtained in step S15 and all the recognition words representing the ski resort names in the "ABCD Prefecture ski resort name dictionary" and the "EFGH Prefecture ski resort name dictionary" are calculated.

In step S18, a decision is made as to whether or not the largest correlation value among the calculated correlation values is equal to or larger than a specific volume. If it is decided to be equal to or larger than the specific value, it is concluded that the word or phrase has been recognized and the operation proceeds to step S19.

In the example, the correlation value relative to the recognition word "F Ski Resort" in the EFGH Prefecture ski resort name dictionary is the largest. If this correlation value is equal to or larger than the specific value, the phrase "F Ski Resort" has been recognized and a successful search of the facility name has been achieved.

In step S19, the recognition word "F Ski Resort" achieving the largest correlation value is echoed back.

In addition, in step S19, the navigation apparatus 100 is notified that a valid facility name has been recognized  
5 before the processing ends. While the navigation apparatus 100 is notified, the coordinates of the facility on the map are also provided to the navigation apparatus 100. Additional information constituted of coordinate data indicating the coordinates of the corresponding  
10 facility is also stored in the recognition dictionary in correspondence to each recognition word. The navigation apparatus 100 displays a road map of the area around the facility on the display device 109 based upon the coordinate data indicating the coordinates of the facility  
15 on the map transmitted via the communication line 211.

If, on the other hand, the largest correlation value is determined to be smaller than the specific value in step S18, it is assumed that the spoken word has not been recognized and the operation proceeds to step S20. In  
20 step S20, "recognition failed" is echoed back by voice, before ending the processing. The navigation apparatus 100 does not engage in any processing, either.

As described above, even if the user erroneously specifies a neighboring prefecture when searching for a  
25 facility located in a given prefecture, the facility can be

referenced in a reliable manner. In the example given above, even if the user erroneously specifies the neighboring "ABCD Prefecture" when searching for "F Ski Resort" located in "EFGH Prefecture," "F Ski Resort" can be referenced with a high degree of reliability. In addition, since it is not necessary to provide recognition words for the names of all the facilities in the country in the work memory, the target facility can be searched efficiently, quickly, accurately and reliably while requiring only a small work memory capacity.

It is to be noted that while an explanation is given above on an example in which "F Ski Resort" is located only in "EFGH Prefecture," there may be another ski resort also called "F Ski Resort" located in "ABCD Prefecture" by coincidence. In such a case, two correlation values achieving equally high levels will be referenced. These search results will be provided to the navigation apparatus 100, and in response, the following display will be brought up on the display device 109. It goes without saying that voice output may be concurrently performed at the voice unit 200.

"1: F Ski Resort (ABCD Prefecture ) or;

2: F Ski Resort (EFGH Prefecture) ?"

The user inputs by voice the number he wishes to choose or inputs the number he wishes to choose through an

input device (not shown) such as a remote control for the navigation apparatus. As a result, even when facilities having identical names are present in neighboring prefectures, the target facility can be selected with ease.

- 5 It is desirable to attach information related to the name of the prefecture in which a given facility is located to each recognition word in the facility recognition dictionary. In such a case, since the name of the prefecture in which the facility is located can be
- 10 displayed with ease in the selection screen described above, the user can make a selection without becoming confused. It goes without saying that the name of the prefecture may be ascertained and displayed by using the prefecture facility name dictionary containing the recognition word.
- 15 It is to be noted that facilities with highly similar names located in neighboring prefectures, e.g., "F Ski Resort" located in "EFGH Prefecture" and "S Ski Resort" located in "ABCD Prefecture," may be handled in a similar manner.

- Second Embodiment -

- 20 An explanation has been given in reference to the first embodiment on an example in which the area is divided in units of individual prefectures in Japan. The dividing units of the area may be individual states in the USA, instead of the prefectures in Japan.

- 25 FIGS. 8A ~ 8C show recognition dictionaries related to

the ski resort category among recognition dictionaries, presenting an example in which the area is divided in units of individual states. They correspond to FIGS. 2A ~ 2C illustrating the first embodiment. In the ski resort state name dictionary shown in FIG. 8B, recognition words corresponding to the names of states in which ski resorts are present are stored. In FIG. 8C, the ABCD State ski resort name dictionary contains recognition words corresponding to the names of ski resorts present in ABCD State and the EFGH State ski resort name dictionary contains recognition words corresponding to the names of ski resorts present in EFGH State. Ski resort name dictionaries corresponding to all the states listed in the ski resort state name dictionary in FIG. 2B are provided in addition to the ABCD State ski resort name dictionary and the EFGH State ski resort name dictionary in FIG. 2C.

In a recognition dictionary, spelling and the voice recognition data (e.g., phonetic symbols (pronunciation symbols)) of recognition words to undergo voice recognition processing are stored. Also, as in the first embodiment, information such as coordinate information is attached in the case of facility names.

FIG. 9 shows a neighboring state table. It corresponds to FIG. 3 illustrating the first embodiment and is similar to FIG. 3 except for that the prefectures in FIG.

3 are replaced by the states. The assignment of neighboring states, too, may be made in a manner similar to the manner in which neighboring prefectures are assigned in the first embodiment.

5 Processing similar to that performed in the first embodiment is implemented by using the ski resort state name dictionary, the individual state ski resort name dictionary and the neighboring state table described above. Consequently, even if a neighboring state is specified by  
10 mistake when searching for a facility present in a given state, the target facility can be referenced with a high degree of reliability.

In the explanation given above, the area is divided in units of individual states in the United States. The  
15 present invention, however, may be adopted in conjunction with an area divided in units of public administrative zone units used in other countries. In other words, recognition dictionaries can be prepared in correspondence to zones (e.g., states, prefectures, districts and  
20 countries) resulting from the divisions made in conformance to the particulars of zone boundaries in the individual countries. In addition, if there are numerous small countries, as in Europe, the area may be divided in units of individual countries, as well.

25 While an explanation is given above in reference to

the embodiments on an example in which the present invention is adopted in a car navigation system, the present invention is not limited to this example. It may be adopted in portable navigation apparatuses instead of navigation apparatuses mounted in vehicles. In addition, it may be adopted in a guide system installed in a building as well. In short, it may be adopted in all types of systems or apparatuses on which a search target among a plurality of search targets present in a plurality of divided zones is specified by voice.

While an explanation is given in reference to the first embodiment on an example in which the area is divided in units of individual prefectures, the present invention is not limited to this example, and the area may be divided in units of smaller municipalities or in units of individual regions such as the Kanto Region, the Tokai Region and the Kinki Region. In addition, it may be divided in units of individual floors or individual specific ranges on a given floor in the case of a guide system installed in a building. Furthermore, the search blocks do not need to represent geographical divisions, either. For instance, if the basic dictionary in FIG. 2A contains a recognition word "Restaurants," the dictionary which is equivalent to the dictionary shown in FIG. 2B may contain recognition words indicating different types of



restaurants such as "French cuisine," "Chinese cuisine" and  
"Japanese cuisine," and the dictionaries that are  
equivalent to those in FIG. 2C may each contain the names  
of restaurants specializing in each cuisine. Also, the  
5 present invention may be adopted effectively when different  
types of "accommodations" are classified as "business  
hotels," "hotels" and "Japanese-style inns." In such a  
case, by assigning "business hotels" and "hotels" to  
classification categories that are similar to each other, a  
10 search can be performed with "business hotels" added as a  
search target when "hotels" is specified. Thus, even if  
"hotels" is erroneously specified to search for "ABC Hotel"  
which is classified as a business hotel, a successful  
search is achieved.

15 In addition, while an explanation is given in  
reference to the embodiments on an example in which a ski  
resort located in a given public administrative zone, the  
present invention is not limited to these particulars.  
Any targets, including street names, airport names and  
20 theme parks can be referenced. In other words, a search  
target may assume any form and its classification block,  
too, may assume any form in correspondence to the  
attributes of the search target.

While an explanation is given above in reference to  
25 the embodiments on a structure achieved by providing the

navigation apparatus 100 and the voice unit 200 as separate units, the present invention is not limited to these particulars and may be adopted in an integrated navigation apparatus having an internal voice unit. In addition, the control program, the recognition dictionaries, the neighboring prefecture table and the like explained above may be provided in a recording medium such as the CD-ROM 111. Furthermore, the control program, the recognition dictionaries and the like may be provided in a recording medium such as a CD-ROM 111 and the system described above may be realized on a computer such as a personal computer or a workstation.

Alternatively, the control program, the recognition dictionaries, the neighboring prefecture dictionaries and the like may be provided via a transmission medium such as a communication line, a typical example of which is the Internet. In other words, the control program and the like may be converted to a signal that is transmitted through a transmission medium. FIG. 10 illustrates how this may be realized. A navigation apparatus 401 is the navigation apparatus explained earlier and has a function of connecting with a communication line 402. A computer 403 is a server computer in which the control program and the like are stored so that the control program and the like can be provided to the 401. The communication line

402 may be a communication line for Internet communication or personal computer communication, or it may be a dedicated communication line. The communication line 402 may be a telephone line or a wireless telephone line such as that for a mobile telephone connection.

While an explanation is given above in reference to the embodiments on an example in which when a successful search of a facility name is achieved in the voice unit 200, the results of the search are provided to the navigation apparatus 100, and in response, the navigation apparatus 100 displays a map of the area around the facility as part of the navigation processing which includes route guidance, the present invention is not limited to these particulars. Various types of navigation processing such as route search and route guidance may be implemented in the navigation apparatus 100 based upon the results of a successful search performed by the voice unit 200.

While an explanation is given above in reference to the embodiments on an example in which a search is performed by using a facility name dictionary prepared by incorporating the prefecture facility name dictionary corresponding to the specified prefecture and a neighboring prefecture facility name dictionary in the RAM, the present invention is not restricted by these particulars. A search may be performed by giving the highest priority to

the specified prefecture with neighboring prefectures assigned with differing priority ranks. In addition, a search may be started using the facility name dictionary corresponding to the prefecture with the highest priority, and the processing may be finished after completing the search if a correlation value achieving a level equal to or higher than a specific level is obtained in referencing the prefecture.

While an explanation is given above in reference to the embodiments on an example in which the search target is specified through voice recognition, the present invention is not restricted by these particulars. It may be adopted when a search target is specified through an input device such as a keyboard, as well. In other words, it may be adopted in all modes of a search executed in units of specific classification blocks instead of handling all the search targets at once.

What is claimed is;

1. A voice reference apparatus that classifies a plurality of search targets into a plurality of division blocks, searches for a search target by first specifying a division block and then specifying said search target and enables specification of, at least, said search target to be made by voice, comprising:

a first storage device in which recognition data related to search targets corresponding to individual division blocks are stored;

a second storage device in which division block-related information indicating one or more other division blocks related to a given division block through a specific relationship is stored;

a recognition data selection device that selects recognition data corresponding to only a certain division block and one or more other division blocks related to said certain division block specified by said division block-related information from said first storage device, when said certain division block has been specified; and

a voice recognition processing device that performs voice recognition based upon voice recognition data generated by using said recognition data selected by said recognition data selection device and audio data

corresponding to said search target specified by voice.

2. A voice reference apparatus according to claim 1,  
wherein:

5       said plurality of division blocks are public  
administrative zones;

          said search target is located in one of said public  
administrative zones; and

          said division block-related information indicates one  
10       or more other public administrative zones related to a  
specified public administrative zone through a specific  
relationship.

3. A voice reference apparatus according to claim 2,  
15       wherein;

          said public administrative zones are each constituted  
of a prefecture.

4. A voice reference apparatus according to claim 2,  
20       wherein;

          said public administrative zones are each constituted  
of a state.

5. A voice reference apparatus according to claim 2,  
25       wherein;

said public administrative zones are each constituted of a country.

6. A voice reference apparatus according to claim 2,  
5 wherein;

said division block-related information indicates one or more other public administrative zones adjacent to a specified public administrative zone.

10 7. A voice reference apparatus according to claim 6, wherein;

said recognition data related to said search target includes information related to a public administrative zone in which said search target is located .

15 8. A voice reference apparatus according to claim 7, further comprising:

a display control device that implements control to display details related to results of a search of said search target on a display device, wherein;

when implementing control to display the details related to the results of the search of said search target, said display control device also displays on said display device information related to the public administrative zone in which said search target is located.  
25

9. A voice recognition navigation apparatus, comprising:  
a voice reference apparatus;  
a map information storage device that stores map

5 information; and

a control device that implements control for providing  
route guidance based upon, at least, results of a search  
performed by said voice reference apparatus and said map  
information, wherein;

10 said voice reference apparatus, which classifies a  
plurality of search targets into a plurality of division  
blocks, searches for a search target by first specifying a  
division block and then specifying said search target and  
enables specification of, at least, said search target to  
15 be made by voice, comprises:

a first storage device in which recognition data  
related to search targets corresponding to individual  
division blocks are stored;

a second storage device in which division block-  
20 related information indicating one or more other division  
blocks related to a given division block through a specific  
relationship is stored;

a recognition data selection device that selects  
recognition data corresponding to only a certain division  
25 block and one or more other division blocks related to said



certain division block specified by said division block-related information from said first storage device, when said certain division block has been specified; and

a voice recognition processing device that performs  
5 voice recognition based upon voice recognition data generated by using said recognition data selected by said recognition data selection device and audio data corresponding to said search target specified by voice.

10 10. A recording medium that records a voice reference control program for searching for a search target specified by voice, by first specifying a division block and then specifying said search target, said control program comprising:

15 an instruction for reading recognition data related to search targets, a plurality of said search targets being classified into a plurality of division blocks;

an instruction for reading data related to division  
20 division blocks related to a given block through a specific relationship;

an instruction for selecting recognition data  
corresponding to only a certain division block and one or  
more other division blocks related to said certain division  
25 block specified by said division block-related information

when said certain division block has been specified; and  
an instruction for implementing a voice recognition  
based upon voice recognition data generated by using said  
recognition data that have been selected and audio data  
5 corresponding to said search target specified by voice.

11. A data signal transmitted in a communication line and  
comprising a voice reference control program for searching  
for a search target specified by voice, by first specifying  
10 a division block and then specifying said search target,  
said control program comprising:

an instruction for reading recognition data related to  
search targets, a plurality of said search targets being  
classified into a plurality of division blocks;

15 an instruction for reading data related to division  
block-related information indicating one or more other  
division blocks related to a given block through a specific  
relationship;

an instruction for selecting recognition data  
20 corresponding to only a certain division block and one or  
more other division blocks related to said certain division  
block specified by said division block-related information  
when said certain division block has been specified; and

an instruction for implementing a voice recognition  
25 based upon voice recognition data generated by using said




## ABSTRACT OF THE DISCLOSURE

A voice reference apparatus that classifies a plurality of search targets into a plurality of division blocks, searches for a search target by first specifying a division block and then specifying the search target and enables specification of, at least, the search target to be made by voice, includes: a first storage device in which recognition data related to search targets corresponding to individual division blocks are stored; a second storage device in which division block-related information indicating one or more other division blocks related to a given division block through a specific relationship is stored; a recognition data selection device that selects recognition data corresponding to only a certain division block and one or more other division blocks related to the certain division block specified by the division block-related information from the first storage device, when the certain division block has been specified; and a voice recognition processing device that performs voice recognition based upon voice recognition data generated by using the recognition data selected by the recognition data selection device and audio data corresponding to the search target specified by voice.

# FIG. 1

## 100 NAVIGATION APPARATUS



## 211 COMMUNICATION LINE

## 200 VOICE UNIT





FIG. 2A

BASIC DICTIONARY



"SKI  
RESORTS"

FIG. 2B

SKI RESORT PREFECTURE  
NAME DICTIONARY





FIG. 2C

ABCD PREFECTURE SKI RESORT  
NAME DICTIONARY



EFCH PREFECTURE SKI RESORT  
NAME DICTIONARY




FIG. 3




FIG. 4A

TARGET PREF. CODE	NEIGHBORING PREF. CODE	
HOKKAIDO	01 AOMORI	02
AOMORI	02 HOKKAIDO	01 IWATE
IWATE	03 AOMORI	04 AKITA
MIYAGI	04 IWATE	05 YAMAGATA
AKITA	05 AOMORI	06 FUKUSHIMA
YAMAGATA	06 IWATE	07 MIYAGI
FUKUSHIMA	07 MIYAGI	08 IBARAKI
IBARAKI	08 FUKUSHIMA	09 GUNMA
TOCHIGI	09 FUKUSHIMA	10 SAITAMA
GUNMA	10 FUKUSHIMA	11 CHIBA
SAITAMA	11 IBARAKI	12 CHIBA
CHIBA	12 IBARAKI	13 YAMANASHI
TOKYO	13 SAITAMA	14 KANAGAWA
KANAGAWA	14 CHIBA	15 YAMANASHI
NIIGATA	15 YAMAGATA	16 FUKUSHIMA
TOYAMA	16 NIIGATA	17 NAGANO
ISHIKAWA	17 TOYAMA	18 Gifu
FUKUI	18 ISHIKAWA	19 Gifu
YAMANASHI	19 GUNMA	20 SAITAMA
NAGANO	20 GUNMA	21 NIIGATA
Gifu	21 TOYAMA	22 ISHIKAWA
SHIZUOKA	22 KANAGAWA	23 YAMANASHI
AICHI	23 NAGANO	24 Gifu
		25 SHIGA

AICHI 23  
SHIZUOKA 22

AICHI 23  
SHIZUOKA 22

AICHI 23  
SHIZUOKA 22

AICHI 23  
SHIZUOKA 22

AICHI 23  
SHIZUOKA 22

AICHI 23  
SHIZUOKA 22

AICHI 23  
SHIZUOKA 22

AICHI 23  
SHIZUOKA 22

AICHI 23  
SHIZUOKA 22



[illegible]

FIG. 5




FIG. 6




FIG. 7








FIG. 10





FIG. 11A  
PRIOR ART


BASIC DICTIONARY



"SKI  
RESORTS"

FIG. 11B  
PRIOR ART


SKI RESORT PREFERENCE  
NAME DICTIONARY



ABCD  
PREFECTURE


FIG. 11C  
PRIOR ART

ABCD PREFECTURE SKI RESORT  
NAME DICTIONARY



"B SKI  
RESORT"

FIG. 11D  
PRIOR ART





**DECLARATION AND POWER OF ATTORNEY - PATENT APPLICATION**

As a below named inventor, I hereby declare that my citizenship, postal address and residence are as stated below; that I verily believe I am the original, first and sole inventor (if only one inventor is named below) or a joint inventor (if plural inventors are named below) of the invention entitled:

**VOICE REFERENCE APPARATUS, RECORDING MEDIUM RECORDING VOICE REFERENCE CONTROL PROGRAM AND VOICE RECOGNITION NAVIGATION APPARATUS**

the specification of which

  X   is attached hereto, or  
 \_\_\_\_\_ was filed on \_\_\_\_\_ as Application Serial No. \_\_\_\_\_ and  
 \_\_\_\_\_ was amended on \_\_\_\_\_ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above. I acknowledge the duty to disclose all information known to be material to patentability as defined in 37 CFR §1.56. I hereby claim foreign priority benefits under Title 35, United States Code §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)

Priority Claimed

<u>11-255981</u>	<u>Japan</u>	<u>09/Sep./1999</u>	<u>xx</u>
(Number)	(Country)	(Day/Month/Year)	
_____	_____	_____	_____
(Number)	(Country)	(Day/Month/Year)	

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose all information known to be material to patentability as defined in 37 CFR §1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application:

_____ (Application Serial No.)	_____ (Filing Date)	_____ (Status)
--------------------------------	---------------------	----------------

I hereby appoint as principal attorneys Martin Fleit, Reg. No. 16,900; Herbert I. Cantor, Reg. No. 24,392; James F. McKeown, Reg. No. 25,406; Donald D. Evenson, Reg. No. 26,160; Joseph D. Evans, Reg. No. 26,269; Gary R. Edwards, Reg. No. 31,824; Jeffrey D. Sanok, Reg. No. 32,169; Richard R. Diefendorf, Reg. No. 32,390; Corinne M. Pouliquen, Reg. No. 35,753; David J. Kulik, Reg. No. 36,576; Paul A. Schnose, Reg. No. 39,361; and H. Thomas Anderton, Jr., Reg. No. 40,895, to prosecute and transact all business in the Patent and Trademark Office connected with this application and any related United States and international applications. Please direct all communications to:

**Evenson, McKeown, Edwards & Lenahan, P.L.L.C.**  
 1200 G Street, N.W., Suite 700  
 Washington, D.C. 20005  
 Telephone: (202) 628-8800  
 Facsimile: (202) 628-8844

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under §1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

**INVENTOR: Yoshikazu HIRAYAMA**

Citizenship: Japan

Post Office Address: C/O XANAVI INFORMATICS CORPORATION, 6-35, Hironodai 2-chome,

Zama-shi, KANAGAWA 228-0012 JAPAN

Residence: Zama-shi, KANAGAWA, JAPAN

28/8/2000

(date)

YOSHIKAZU HIRAYAMA

(signature of 1st inventor)

**DECLARATION AND POWER OF ATTORNEY**

Page 2

Attorney Docket No. \_\_\_\_\_

**INVENTOR:** Yoshiyuki KOBAYASHI

Citizenship: Japan

Post Office Address/ C/O XANAVI INFORMATICS CORPORATION, 6-35, Hironodai 2-chome,  
Zama-shi, KANAGAWA 228-0012 JAPAN

Residence: Zama-shi, KANAGAWA, JAPAN

25/AUG/2000

(date)

Yoshiyuki Kobayashi

(signature of 2nd inventor)

**INVENTOR:**

Citizenship:

Post Office Address/

Residence:

\_\_\_\_\_  
(date)

\_\_\_\_\_  
(signature of 3rd inventor)

**INVENTOR:**

Citizenship:

Post Office Address/

Residence:

\_\_\_\_\_  
(date)

\_\_\_\_\_  
(signature of 4th inventor)

**INVENTOR:**

Citizenship:

Post Office Address/

Residence:

\_\_\_\_\_  
(date)

\_\_\_\_\_  
(signature of 5th inventor)

**INVENTOR:**

Citizenship:

Post Office Address/

Residence:

\_\_\_\_\_  
(date)

\_\_\_\_\_  
(signature of 6th inventor)

**INVENTOR:**

Citizenship:

Post Office Address/

Residence:

\_\_\_\_\_  
(date)

\_\_\_\_\_  
(signature of 7th inventor)